


Mercury SEL Type (1~2a Mercury Relay)

■ Part number · Feature

● LDW-**M**-** **



- High current and printed circuit board type

■ Performance

Specifications	Item	Standard
Contact Specifications	Contact Form	1a (make mercury)
	Contact Rating	50W
	Max. Switching Voltage	DC. 500V
	Max. Switching Current	1 A
	Max. Carry Current	2 A
	Contact Resistance	100 mΩ MAX (Initial)
Electrical Specifications	Breakdown Voltage	Open Contacts DC. 1000V (1 min) Contact to Coil DC. 500V (1 min) Contact to Shield DC. 500V (1 min) Coil to Shield DC. 500V (1 min)
	Insulation Resistance	Between all isolated pins $1 \times 10^{10} \Omega$ MIN (DC. 100V)
	Capacitance	Open Contacts 1.0pF TYP. Contact to Shield 0.1F MAX. (Shield guarding)
	Thermal Electromotive Force	60 μV TYP.
	Operate Time	(1 Pulse) 2.5 mS MAX. (at Nominal Voltage)
	Release Time	(1 Pulse) 2.5 mS MAX. (at Nominal Voltage)
Mechanical Specifications	Vibration	20G (0 to 55Hz 1.5mm)
	Shock	30G (11ms 1/2 Sin Wave)
Environment	Operating Temperature	-10°C to +60°C
Life Expectancy	Mechanical	1X10 ⁹ MIN. Operations
	Electrical	DC. 10mV-10 μA 1X10 ⁹ MIN. Operations (R.L.)

■ Coil Specifications

Contact Form	Part Number	Nominal Voltage DC. $\pm 10\%$ (V)	Coil Resistance $\pm 10\%$ (Ω) at 20°C	Nominal Current (mA)	Must Operate Voltage MAX. (V) at 20°C
1a	LDW-1M-24 (D, N)	24	1600	15.0	16.8
	LDW-1M-12 (D, N)	12	400	30.0	8.4
	LDW-1M-05 (D, N)	5	75	67.0	3.8
2a	LDW-2M-24 (D, N)	24	1000	24.0	16.8
	LDW-2M-12 (D, N)	12	250	48.0	8.4
	LDW-2M-05 (D, N)	5	50	100.0	3.8

■ Dimensions /Terminal Identification (Unit:mm)

Dimensions	Terminal Identification
() : dimensions of N-type with magnetic-shield weight 1M...about 4.2gr. N-type about 6.0gr. 2M...about 5.6gr. N-type about 7.5gr.	TOP VIEW Note: Mount a relay to be UP indication arrow within $\pm 30^\circ$ from a plumb line.